



WARNING: This product can expose you to chemicals including lead, which is known to the State of California to cause cancer. For more information, go to www.P65Warnings.Ca.gov

Leonard 4 Point Digital Monitoring System with Alarm

Unit includes:

- Four (4) Temperature Probes - Range: -148°F to 212°F Resolution: 1°F
- Audio & visual alarms
- User adjustable high & low temperature alarm set points
- Alarm delay period to prevent nuisance alarms
- Remote alarm contacts (SPDT) with adjustable relay period
- Battery Back-up, 3.7V, 1150 mAh Li-polymer cell with built in constant current / constant voltage charger with automatic recharge and "low battery" indication
- 4 each 100 ohm RTD sensors, 4" length with 10' lead wire
- UL listed 120 VAC power supply w/10' cord, less than 1 amp
- Mounting bracket
- NIST traceable certificate of calibration
- 10/100 Ethernet Connection
- Web Server Interface for Setup & Commissioning
- Unit can send an E-mail transmission of alarms for up to 8 contacts
- Unit can send an E-mail report daily with temperatures readings over the previous day
- RoHS compliant

Product is non-cancellable and non-returnable from date from order with factory. Signed submittal required with purchase order.

Engineer's Approval	Job # _____
	Arch/Eng. _____
	Contractor _____



1360 Elmwood Avenue, Cranston, RI 02910 USA
 Phone: 401.461.1200 Fax: 401.941.5310
 Email: info@leonardvalve.com
 Web Site: <http://www.leonardvalve.com>

LMS-188-4P ACCESSORIES

RDU – Remote Display Unit

- Activated when LMS-188-4P relay switch is in alarm mode
- Alarm Delay Module with yellow, red, green LED indicators
- UL listed 100-240VAC power supply with 10' cord, less than 1 amp
- Unit includes 9V NiMH rechargeable battery back up
- User selectable timer
- VELCRO mounting strips provided
- Recommended maximum distance from controller to RDU is 500'

SCO – Solenoid Control Option

- For use with LMS-188-4P relay switch
- Galvanized box with dimensions 6" Wide x 6" High x 4" Deep,
- Solid state relay and terminal strip mounted and wired
- UL listed 100-240VAC power supply with 10' cord, less than 1 amp
- For either normally open or normally closed operation
- For use with 24-240 VAC solenoids only

SUFFIX RDU



SUFFIX SCO

