

# ECO HAND SHOWERS

For Wall Grab bars, see page 2

## 100P

Hand spray with non-positive push button shut-off  
Braided stainless steel flexible hose, 60"  
2 wall hooks  
Double check valve backflow preventer  
Supply elbow and flange  
2.5 GPM (9.5 l/min.) max. flow rate

## 105P

•Same as above except 1.5 GPM (5.7 l/min.)



## 101P(G)

ADA Hand spray with non-positive push button shut-off  
Braided stainless steel flexible hose, 60"  
24" (610mm) glide rail  
Soap dish, removable  
Double check valve backflow preventer  
Supply elbow and flange  
2.5 GPM (9.5 l/min.) max. flow rate

## 115P(G)

•Same as above except 1.5 GPM (5.7 l/min.)



## 101P

Hand spray with non-positive push button shut-off  
Braided stainless steel flexible hose, 60"  
24" (610mm) slide bar  
Double check valve backflow preventer  
Supply elbow and flange  
2.5 GPM (9.5 l/min.) max. flow rate

## 115P

•Same as above except 1.5 GPM (5.7 l/min.)



## OPTIONAL (fits all models):

SUFFIX RV– White vinyl hose

SUFFIX 72 – 72" Hose in place of 60"

**NOTE: SUFFIX QD – OBSOLETE, no replacement**

**NOTE: SUFFIX -30 – OBSOLETE, use standard 24"**



**WARNING:** This product can expose you to chemicals including lead, which is known to the State of California to cause cancer. For more information, go to [www.P65Warnings.ca.gov](http://www.P65Warnings.ca.gov)

## 100P / 105P



## 101P(G) / 115P(G)



## 101P / 115P



1360 Elmwood Avenue, Cranston, RI 02910 USA

Phone: 401.461.1200 Fax: 401.941.5310

Email: [info@leonardvalve.com](mailto:info@leonardvalve.com)

Web Site: <http://www.leonardvalve.com>

# WALL GRAB BARS & HAND SHOWERS SETS

## 62001A

24" (61 cm) ADA wall grab bar, stainless steel, 1.5" (38mm) outside diameter, concealed screw mounting system (mounting hardware included)

Slide mechanism operable by left hand, right hand, or closed first, 2.65" (67mm) lever, meets Handicapped Accessibility Standard of less than 5lb handle operating force and can swivel to ensure easy reach

Withstands 1000 lb pull (NOTE: Grab Bar must be securely attached to wall or backing to provide safety)

Wall Grab bar can be securely mounted at 90 degree angle

Hand spray with non-positive push button shut-off

Braided stainless steel flexible hose, 60"

2 wall hooks

Double check valve backflow preventer

Supply elbow and flange

2.5 GPM (9.5 l/min.) max. flow rate



## 62001A-1.5

- Same as above except 1.5 GPM (5.7 l/min.)



## 62003A

- Same as above except 36" grab bar (91 cm)

## 62003A-1.5

- Same as above except 36" grab bar (91 cm) & 1.5 GPM (5.7 l/min.)



### OPTIONAL (fits all models):

SUFFIX RV– White vinyl hose

SUFFIX 72 – 72" Hose in place of 60"



1360 Elmwood Avenue, Cranston, RI 02910 USA

Phone: 401.461.1200 Fax: 401.941.5310

Email: [info@leonardvalve.com](mailto:info@leonardvalve.com)

WEB: <http://www.leonardvalve.com>